

# H Series Wardrobe Specifications

## A. UNIT FEATURES

1. All units shall be by-pass sliders with bottom mounted rollers.
2. Top guides shall be fixed nylon assembly for silent operation.
3. Bottom rollers shall be heavy duty nylon mounted in adjustable brackets with a height adjustment of  $\pm 1/8$ ".
4. Frame shall be anodized aluminum.
5. Two and three panel configurations available.
6. Vertical rails shall have full length vinyl bumpers.
7. Detailed instruction sheets and cross sections with custom unit fabrication formulas.
8. 24 hour product information and support via the **Alumax Bath Enclosures Website** ([www.alumaxbath.com](http://www.alumaxbath.com)).

## B. UNIT VALIDITY

1. Mechanical test: Moving parts or components subject to wear are cycle tested to simulate 20 years of use.
2. Quality: Alumax Bath Enclosures are produced in accordance with procedures specified by ISO 9000.

## C. MATERIALS AND CONSTRUCTION

1. Size Limitations:  
Maximum allowable size of 2 panel unit = 96" wide x 96" tall.  
Maximum allowable size of 3 panel unit = 144" wide x 96" tall.  
(Maximum allowable size does not imply that components are necessarily available to construct the largest size allowable.)
2. Alloy and Temper: Extruded aluminum shall be 6463-T6 alloy per ASTM B 221. This alloy is designed to accept a bright finish after anodizing. Used for decorative trim applications, machineable, polished, and anodized - also heat treatable.

<b>MECHANICAL PROPERTIES OF 6463-T6 (b)</b>					
<b>Thickness in inches (b)</b>	<b>Tensile Strength - ksi</b>				<b>Elongation percent min. in 2 in. or 4D</b>
	<b>Ultimate</b>		<b>Yield</b>		
	<b>min.</b>	<b>max.</b>	<b>min.</b>	<b>max.</b>	
Up thru 0.124	30	..	25.0	..	8
0.125 - 1.000	30	..	25.0	..	10

- a. Hardness of 6463-T6 on Rockwell B scale: 20-50.
  - b. T6 temper designates a material that is thermally treated to produce stable tempers then solution heat treated and artificially aged. For complete temper designation consult technical publications ANSI 35.1 or the Aluminum Association publication, Aluminum Standards and Data.
  - c. The thickness of the cross-section from which the tension test specimen is taken determines the applicable mechanical properties. The data base and criteria upon which these mechanical property limits are established are outlined in the Aluminum Association publication Aluminum Standards and Data (ASD) Section 6, "Mechanical Properties".
3. Metal Gauge: The nominal wall thickness of individual aluminum extruded components for this unit varies with structural needs.

<b>Component</b>	<b>Description</b>	<b>Nominal Wall Thickness</b>
SC-591	Header	.070"
SC-592	Curb	.062"
SC-593	Top Rail	.062"
SC-594	Bottom Rail	.062"
SC-595	Side Rail	.062"

4. Tolerances: Tolerances on all aluminum extruded components shall comply with Aluminum Association requirements unless otherwise specified.
5. Hardware: All hardware parts that are incorporated in the product shall be of aluminum, stainless steel, or other corrosion resistant material(s) compatible with aluminum. Cadmium or zinc-plated parts, where used, shall be in compliance with ASTM A 164-71 or 165-74. Nickel or chrome-plated parts, where used, shall be in compliance with ASTM B 456.71, SC2. Stainless material should have a preference of a 310 alloy with a 410 alternative.
  - a. Fasteners to follow International Fasteners Institute standard B18.6.3 for Slotted and Recessed Head Machine Screws and Metallic Drive Screws or B18.6.4 for Slotted and Recessed Head Tapping Screws and Metallic Drive Screws.

<b>b. MECHANICAL PROPERTIES OF BUMPER VINYL Plasticized, filled with Shore A Durometer Hardness of 65</b>	
Tensile Break Strength	1100 psi
Ultimate Elongation	360%
Specific Gravity 23/23 C	1.39
Shore "A" Hardness Initial @ 10 sec.	65 61
Brittleness Point, F 50% Failure @	-33

6. Glazing Vinyls: Vinyls and other glazing seal materials shall be of material compatible with aluminum, be resistant to water and common household chemicals and shall secure the glass in the surrounding frame.

<b>a. MECHANICAL PROPERTIES OF GLAZING VINYL Plasticized, filled with Shore A Durometer Hardness of 60</b>	
Tensile Break Strength	920 psi
Ultimate Elongation	600%
Specific Gravity 23/23 C	1.28
Shore "A" Hardness Initial @ 10 sec.	61 58
Brittleness Point, F 50% Failure @	-6

7. Glazing Materials: All glazing materials to be safety back mirror with a nominal thickness of .156", .188", or .250" to conform to Federal Standard CPSC 16 CFR 1201 Category 2, Safety Standard for Architectural Glazing Materials. Dimensional tolerances shall conform to ASTM C 1036-85 and ASTM C 1048-85.
8. Finish Specifications (Anodized): The finish on anodized aluminum components shall conform to the following Aluminum Association Specifications:
- a. Silver: AA-M21-C31-A21 for buffed, clear, bright anodized aluminum.
  - b. Gold: AA-M21-C31-A23 for buffed, colored, bright anodized aluminum.

Anodized aluminum components are tested or inspected for thickness of anodic coating (.00015" min.\.00030" max.), color range variation, and integrity of the anodic seal.

**NOTE:** The finished surface of anodized aluminum parts can be damaged by harsh cleansers. In particular, glass cleaners or other cleaning products with a PH of less than 7 or more than 9 can damage the anodized finish with prolonged exposure.