

ALUMAX

BATH ENCLOSURES

by Sapa

Tel: 800-643-1514
Fax: 870-234-3181

640/650 Slider Shower Door-Framed

www.alumaxbath.com

Product Features

Available in standard and custom configuration
Tempered safety glass
Adjustable sealed heavy duty ball bearing rollers
Up and down adjustment of panels is $\pm .156$
Safety tee-lock wall jamb to header connection
Molded jamb bumpers with concealed fasteners
Molded nylon panel guide of sufficient height to prevent the accidental dislodging of interior panel

Options

Anti-jamb header insert
Wall fill
Curb fill
Glass patterns
Finish



Calculations

Maximum allowable width of unit = 72
Maximum allowable height of unit = 72

Glass Size

Width = $(\text{Unit Width} \div 2) - 2$
Height = $\text{Unit Ht.} - 4 \frac{1}{2}$

Metal Cuts

SC-556 tub track = $\text{Unit width} - \frac{1}{16}$
SC-805 towel bar = $\text{Bottom rail} - 1 \frac{11}{16}$
SC-881 header = $\text{Unit width} - \frac{1}{16}$
SC-882 top rail = $(\text{Unit width} \div 2) - \frac{1}{8}$
SC-883 bottom rail = $(\text{Unit width} \div 2) - \frac{1}{8}$
SC-884 side rail = $\text{Unit ht.} - 2 \frac{5}{8}$
SC-896 wall jamb = $\text{Unit ht.} - 1 \frac{1}{2}$

640/650 Parts List

- A. 1 Tub Track with Vinyl
- B. 2 Wall Jamb
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Truss Head Screws
- E. 2 Nylon Spacers
- F. 1 Header
- G. 2 Glazed Panels
- H. 4 Nylon Roller Bearings
- J. 4 #8-32 x 3/8 Hex Head Screws
- K. 4 Towel Bar Trim Rings
- L. 4 Towel Bar Brackets
- M. 2 Towel Bars
- N. 2 #10-24 x 7/8 Truss Head Screws
- P. 2 #10-24 x 1 1/8 Flat Head Screws
- R. 2 Acrylic Finger Pulls
- S. 2 Alumax Decals
- T. 1 Nylon Bottom Guide
- U. 1 #6 x 3/8 Pan Head Screw
- V. 2 Stainless Bumper Inserts
- W. 2 Soft Jamb Bumpers
- X. 1 Vinyl Silencer

